

IP DESKTOP STATION

WITH VIDEO DISPLAY (TOUCHSCREEN) AND HANDSET



when communication is **critical**

FEATURES

- **Designed to deliver CCoIP – Critical Communication over IP**
- **Call queue according to priority and time of call, 256 priority levels**
- **Ten DAKs provide single-touch access to stations, group calls, audio monitoring, public address zones, radio channels and telephone lines**
- **Comes with handset for private conversations**
- **Superb audio quality – high bandwidth codec, active noise cancellation, acoustic echo cancellation and high output power amplifier**
- **Remote software upgrade, configuration and monitoring**



DESCRIPTION

The STENTOFON IP Desktop Station with Video Display is an intercom unit designed to be used in a control room or similar type of environment. The station comes with a 3.5" LCD touchscreen display with the capability of displaying pictures from an IP video camera.

Using the station in conjunction with the IP Video & Audio Intercom Wall Station makes an ideal solution for security communication.

Up to 48 video sources can be stored in the onboard directory and readily available even when not in conversation.

It features a large high-contrast display with backlight that allows critical information about connections to be shown clearly. The handset allows the user to switch from private conversation to open discussion in handsfree mode. Four touchscreen Navigation Keys and ten Direct Access Keys (DAK) provide single-touch access to stations, group calls, audio monitoring, public address zones, radio channels and/or the opening of doors and gates.

The station connects directly to the IP network, making it easy to deploy anywhere at any distance. The built-in web server allows monitoring, configuration and software updates over the IP network, making the maintenance of remotely located stations hassle-free. Designed for CCoIP®, the station offers a set of critical communication features such as group call, call priority, and speaker volume override. This enables the delivery of instant, efficient, and secure voice and data services in an IP environment.

www.stentofon.com

Zenitel Norway AS
Sandakerveien 24C, P.O. BOX 4498 Nydalen
NO-0403 Oslo, Norway

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1408001635	IP desktop station with video display (touchscreen) and handset	0.7 kg
1408000635	IP Desktop station with video display (touchscreen) - (ON REQUEST)	

IP DESKTOP STATION WITH VIDEO DISPLAY (TOUCHSCREEN) AND HANDSET

SPECIFICATIONS

Connections and Interfaces	
Ethernet	1 x RJ45 10/100 Mbps with PoE
Characteristics and Functions	
IP protocol	IP v4 – TCP – UDP – HTTPS – TFTP – RTP – RTCP – DHCP – SNMP – DiffServ – TOS – STENTOFON CCoIP - SIP
LAN protocol	Power over Ethernet (IEEE 802.3 a-f) VLAN (IEEE 802.1pq) / network access control (IEEE 802.1x) STP (IEEE 802.1d) / RSTP (IEEE 802.1d-2004)
Audio	Wideband 200Hz – 7kHz (G.722) / telephony 3.4kHz (G.711) Acoustic echo cancelling / open duplex / adaptive jitter filter / Active noise filtering 1.5 W speaker output @ 8 Ohm
Video	Only supported in AlphaCom environments Codecs supported: MJPEG Resolution: 320 x 240 (qVGA)
Management	HTTPS (web interface) DHCP and static IP Automatic remote update Centralized monitoring Status LED's
Display	3.5" Transmissive TFT with touchscreen panel Active area 70 x 52.5mm 320 x 240 dots 262.000 colors LED backlight (white)
Physical Characteristics	
Dimensions (WxHxD)	225 x 75 x 176 mm
Operational voltage	Power over Ethernet: IEEE 802.3 a-f, class 0
Power input	Circa 10 W
Environmental conditions	-20°C to +55°C
Weight	Circa 0.7 kg

Connexus Communications Limited
Unit D2, Baldonnell Business Park
Naas Road, Dublin 22, Ireland
T: 00 353 1 4105866, F: 00 353 1 4105867
info@connexus.ie Visit us at www.connexus.ie



ITEM NUMBER 1408001635
DOC NO. A100K11501
18.3.2014

sales@stentofon.com



Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. STENTOFON and VINGTOR products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel – All rights reserved.